



A=0.75 m

U SLUČAJU DA JE SIGURNOSNA OGRADA PREKINUTA NA DUŽINI KRAĆOJ OD 200m, SMEROKAZI SE POSTAVLJAJU U ISTU LINIJU SA SVETLOSNI ODBOJNICIMA NA ZAŠTITNOJ OGRADI.

IN THE EVENT THAT THE GUARD RAIL IS INTERRUPTED FOR A DISTANCE OF LESS THAN 200m, THE SAFETY POSTS ARE PLACED ON THE SAME LINE AS THE ILLUMINATED BARRIERS ON THE GUARD RAIL.

POSTAVLJANJE SMEROKAZA U ODNOSU NA VERTIKALNI I HORIZONTALNI TOK TRASE
PLACEMENT OF SAFETY POSTS IN RELATION TO THE VERTICAL AND HORIZONTAL COURSE OF THE ROUTE

SREDNJI RADIJUS HORIZONTALNE KRIVINE MEAN RADIUS OF HORIZONTAL CURVE	MEĐUSOBNO ODSTOJANJE SMEROKAZA [m] DISTANCE BETWEEN SAFETY POSTS [m]			
	U KRIVINI IN CURVE	PRVI SMEROKAZ FIRST SAFETY POST	DRUGI SMEROKAZ SECOND SAFETY POST	TREĆI SMEROKAZ THIRD SAFETY POST
20 - 50	4	8	12	24
nad 50 - 100	8	12	24	-
nad 100 - 300	12	24	24	-
nad 300 - 500	24	24	-	-
nad 500	24	-	-	-

SREDNJI RADIJUS HORIZONTALNE KRIVINE MEAN RADIUS OF HORIZONTAL CURVE	MEĐUSOBNO ODSTOJANJE SMEROKAZA [m] DISTANCE BETWEEN SAFETY POSTS [m]			
	U KRIVINI IN CURVE	PRVI SMEROKAZ FIRST SAFETY POST	DRUGI SMEROKAZ SECOND SAFETY POST	TREĆI SMEROKAZ THIRD SAFETY POST
100 - 250	8	12	24	24
nad 250 - 800	12	24	24	-
nad 800 - 3000	24	24	-	-
nad 3000	24	-	-	-

br./no.	promena/change	datum/date	ime/name

klijent/client:			
naslov/title: SRSDD Standardni crteži putnih detalja u Republici Srbiji SRSDD Serbian road standard detail drawings			
crtež/drawing: Detalji postavljanja smerokaza Detail drawing of placement of delineator posts			
razmera/scale: 1:50	datum/date: 30.04.2012	strana/page: 2.2	